

Uniden®

UHF CB MOBILE
80 Channel* | 5W

UH5060



Mount
Anywhere



Mini Compact
Size



Dual
Speakers



Remote
Speaker Mic



5 Year Warranty^A

BUILT RUGGED
FOR AUSTRALIAN & NZ CONDITIONS

Uniden®

UHF CB MOBILE
80 Channel* | 5W **UH5060**



Mount Anywhere



Mini Compact Size



Dual Speakers



Remote
Speaker Mic



INCLUDED IN THE BOX

1 x UH5060 Radio
1 x Remote Speaker MIC
1 x Extension Cable
1 x Microphone Hanger
1 x DC Power Cord
1 x Mounting Bracket
1 x Owner's Manual

80 UHF Narrowband Channels*:

Choose from up to 80 frequencies to transmit and receive messages.

Mini Compact Size: 24mm (H) x 100mm (W) x 95mm (D).

Remote Speaker Microphone with built-in Large LCD Display:

Control all functions and features remotely, including volume and power on/off.

LCD Backlight, Brightness and Contrast Controls

5W Transmission Power: Maximum transmit power.

Dual Speaker with Synchronised

Volume: Speaker at the Base and Microphone

Extension Cable: Use the cable extension and keep the radio hidden from view.

Signal Strength and RF Power (S/RF) Meter

Instant Channel Programming and Recall: Program any channel as the Instant priority channel and recall it at the touch of a button located on the mic.

Open Scan: This scan mode scans all channels in memory and locks on any active channel.

Group Scan: This scan mode allows the user to select the channels they wish to monitor/listen to in a group, along with a priority channel (priority watch).

Dual Watch: Allows you to monitor the priority channel for activity every two seconds while monitoring another UHF channel at the same time.

Monitor On/Off Function

Duplex Capability: Allows the radio to operate via a local repeater station, if available, which re-transmits your signal over a wider area. Up to an extra 30 – 100km depending on location, height and availability of local repeater station.

Key Beep On/Off Function

Busy Channel Lock-out Function: Disables your transmitter while activity is detected on the channel.

Roger Beep Function On/Off:

Confirmation tone indicates the completion of your transmission.

Call Tone Function: Choose from one of 5 wake-up tones to initiate your transmission with the touch of one microphone button.

Auto Squelch: Adjustable 3 Level Auto Squelch function.

Volume Control: Adjustable volume control levels (0 – 7).

External Speaker Jack

CTCSS (Continuous Tone Coded Squelch system) and DCS (Digital Coded Squelch) Codes: Choose from 38 (CTCSS) and 104 (DCS) digital codes that can be sent with your transmission. The code is recognized by the selected receivers enabling them to receive the transmission. Receivers that do not recognize the code remain silent therefore blocking out unwanted conversations.

Designed & Engineered in Japan

Built Rugged for Australian and New Zealand Conditions

* Please note CH 22 & 23 are used for telemetry and telecommand applications, voice communications are not permitted on these channels and transmission is inhibited. CH 61, 62 & 63 are for future use and are receive only channels.

△ One year warranty on any included accessories. Specifications subject to change without notice.

For full range & details call 1300 366 895,
scan QR code or visit uniden.com.au



@UnidenAustralia



facebook.com/Uniden

